

IDROPULTRICI AD ACQUA FREDDA

COLD WATER HIGH PRESSURE CLEANER

NETTOYEUR HAUTE PRESSION EAU FROIDE

Serie FE/P

COD.	MODELLI MODELS MODÈLES	PRESSIONE PRESSURE PRESSION BAR	PORTATA DELIVERY DEBIT Lt. h.	POTENZA-POWER PUISSANCE HP V230/50 V400/50	POMPA PUMP POMPE r.p.m.	BY-PASS	TST
ML 5731	FE/P 150C	130/150	480	3 -	2800	-	STANDARD

COD.	INCLUSO	INCLUDED	INCLUS
AR 1271960	Tubo lancia mt. 8	8 mt. hose lance	Tube lance mt. 8
AR 334	Pistola con prolunga cm 37	Washing gun equipped with a 37 cm. extension	Pistolet avec rallonge 37 cm.
AR 40039	Terminale lancia cm 70 con testina detersivo	70 cm. lance end section with cleanser head	Section terminale lance 70 cm.

CARATTERISTICHE COSTRUTTIVE	TECHNICAL FEATURES	DETAILS TECHNIQUES
Detersivo in bassa pressione	Low pressure cleanser	Détergent basse pression
Alimentazione acqua diretta in pompa	Water supply direct into the pump	Alimentation eau directe dans la pompe
Serbatoio detersivo lt. 2	Lts. 2 cleanser tank	Réservoir détergent lts. 2



SERIE FE/D

COD.	MODELLI MODELS MODÈLES	PRESSIONE PRESSURE PRESSION BAR	PORTATA DELIVERY DEBIT Lt. h.	POTENZA-POWER PUISSANCE HP V230/50 V400/50	POMPA PUMP POMPE r.p.m.	Kg.	VERSION BY-PASS	VERSION T.S.T.
ML 5220	FE/D 120M	120	660	3 -	1450	44	DI SERIE	STANDARD
ML 5230	FE/D 150M	150	900	- 5,5	1450	45		
ML 5648	FE/D 200M	200	900	- 7,5	1450	58		
ML 5768	FE/D 151	150	900	- 5,5	1450	62		
ML 5769	FE/D 201	200	900	- 7,5	1450	62		

COD.	ACCESSORI A RICHIESTA	OPTIONALS	OPTIONAL
CA 3459	Macchine con vol. 230-380-440 - Hz 60	230-380-440 Volt / 60 Hz Machine	Machine 230-380-440 Volt / 60 Hz
CA 1783	Valvola di sicurezza termica 0°-64° C	0°/-64° C Thermal safety valve	Valvule de sécurité thermique 0°/-64°C
CA 4072	Comando TST con flussostato	TST control with flowmeter	Contrôle TST avec flow-switch

COD.	INCLUSO	INCLUDED	INCLUS
CA 1332	Tubo lancia mt. 10	10 mt. lance	Tube lance 10 mts.
CA 2760	Pistola con prolunga cm 37	Washing gun equipped with a 37 cm. extension	Pistolet avec rallonge 37 cm.
CA 2765	Termine lancia cm 70 con testina detersivo	70 cm. lance end section with cleanser head	Section terminale lance 70 cm. avec tête détergent

CARATTERISTICHE COSTRUTTIVE	TECHNICAL FEATURES	DETAILS TECHNIQUES
Detersivo in bassa pressione	Low pressure cleanser	Détergent basse pression
Alimentazione acqua diretta in pompa	Water supply direct into the pump	Alimentation eau directe dans la pompe
Serbatoio detersivo lt. 5	5 lts. cleanser tank	Réservoir détergent 5 lts.