

IDROPULTRICI AD ACQUA FREDDA

COLD WATER HIGH PRESSURE CLEANER

NETTOYEUR HAUTE PRESSION EAU FROIDE

Serie FE/S

COD.	MODELLI MODELS MODÈLES	PRESSIONE PRESSURE PRESSION BAR	PORTATA DELIVERY DEBIT Lt. h.	POTENZA-POWER PUISSANCE HP		POMPA PUMP POMPE r.p.m.	Kg.	BY-PASS		TST		
				V230/50	V400/50			DI SERIE	STANDARD	A RICHIESTA	ON REQUEST	SUR DEMANDE
ML 5763	FE/S 150	150	900	—	5,5	1450	64	DI SERIE	STANDARD	A RICHIESTA	ON REQUEST	SUR DEMANDE
ML 2785	FE/S 160	160	1080	—	7,5	1450	75					
ML 5260	FE/S 200	200	900	—	7,5	1450	75					
ML 5270	FE/S 223	200	1260	—	10	1450	94					
ML 5649	FE/S 233	200	1800	—	15	1450	112					
ML 5694	FE/S 318	300	1080	—	15	1450	107					

COD.	ACCESSORI A RICHIESTA	OPTIONALS	OPTIONAL
CA 3459	Macchine con vol. 230-380-440 - Hz 60	230-380-440 Volt / 60 Hz Machine	Machine 230-380-440 Volt / 60 Hz
CA 4073	Comando TST con flussostato (solo FE/S 150/160/200/223)	TST control with flowmeter (only for FE/S 150/160/200/223)	Contrôle TST avec fluxmètre (seulement pour FE/S 150/160/200/223)
CA 3984	Cofanatura inox	Stainless steel covering	Couverture en acier inox
CA 3710	Pompa inox per acqua calda max 80°C (FE/S 160)	Hot water stainless steel pump max. 80° C (FE/S 160)	Pompe en acier inox pour eau chaude max. 80° C (FE/S 160)
CA 4085	Vaschetta acqua PVC lt 18 (no serbatoio detersivo)	18 lts. PVC water tank (no cleanser tank)	Bac eau en PVC 18 lts. (réservoir détergent exclus)
CA 2792	Quadro comando total stop temporizzato (avviamento marcia arresto V24)	Total stop control panel equipped with timer (V24 start-up/stop)	Tableau de contrôle total stop temporisé (démarrage - arrêt V24)
CA 2448	Avvolgitubo manuale Bar 250 in PVC per tubo mt 30 (senza tubo)	250 bar manual PVC pipe rewriter for 30 mt. Pipe (no pipe included)	Tambour à tuyaux manuel 250 bar en PVC pour tuyau 30 mt. (sans tube)

COD.	INCLUSO	INCLUDED	INCLUS
CA 771	Tubo lancia mt. 10	10 mt. hose lance	Tube lance 10 mts.
CA 2761	Pistola con prolunga cm 37	Washing gun equipped with a 37 cm. extension	Pistolet avec rallonge 37 cm.
CA 2765	Termine lancia cm 70 con testina detersivo	70 cm. lance end section with cleanser head	Section terminale lance 70 cm. Avec tête détergent

CARATTERISTICHE COSTRUTTIVE	TECHNICAL FEATURES	DETAILS TECHNIQUES
Detersivo in bassa pressione	Low pressure cleanser	Détergent basse pression
Alimentazione acqua diretta in pompa	Water supply direct into the pump	Alimentation eau directe dans la pompe
Serbatoio detersivo incorp. lt. 18	18 lts. cleanser tank	Réservoir détergent 18 lts.
Valvola sicurezza termica montata (no con TST)	Thermal safety valve already assembled (not available with TST)	Valvule de sécurité thermique montée (TST exclus)

