

IDROPULITRICI AD ACQUA CALDA

HOT WATER HIGH PRESSURE CLEANERS

NETTOYEUR HAUTE PRESSION EAU CHAUDE

Serie WH/S-V

COD.	MODELLI MODELS MODELES	PRESSIONE PRESSURE PRESSION BAR	PORTATA DELIVERY DEBIT Lt. h.	POTENZA-POWER PUISSANCE HP V230/50 V400/50	POMPA PUMP POMPE r.p.m.	TEMP. ACQUA WATER TEMP. TEMPER. EAU	Kg.	VERSION BY-PASS	VERSION T.S.T.
ML 5774	WH/S-V 165 ED	160	900	- 5,5	1450	30°-95°	145	A RICHIESTA ON REQUEST SUR DEMANDE DI SERIE STANDARD	
ML 5767	WH/S-V 205 ED	200	900	- 7,5	1450	30°-95°	156		
ML 5748	WH/S- V 165	160	900	- 5,5	1450	30°-95°-140°	156		
ML 5749	WH/S- V 205	200	900	- 7,5	1450	30°-95°-140°	156		
ML 5750	WH/S- V 225	200	1260	- 10	1450	30°-85°-130°	195		
ML 5761	WH/S- V 305	300	1080	- 15	1450	30°-90°-130°	215		

COD.	ACCESSORI A RICHIESTA	OPTIONALS	OPTIONAL
CA 3459	Macchine volt 230-380 Hz 60	230-380 Volt / 60 Hz Machine	Machine 230-380 Volt / 60 Hz
CA 4231	Macchine volt 440 Hz 60 (no WH/S-V 205E)	440 Volt / 60 Hz Machine (WH/S-V 205E not incl)	Machine 440 Volt / 60 Hz (WH/S-V 205E pas inclus)
CA 3711	Dispositivo comando total stop (ST30) solo per WH/S 205E - 165E	Total Stop control device (ST30) only for WH/S 205E - 165E	Dispositif de contrôle total stop (ST30) seulement pour WH/S 205E - 165E
CA 2743	Dispositivo anticalcare liquido - fustino lt 2	Anti-scaling liquid - 2 lts tank	Dispositif anti-calcaire - réservoir lt 2
CA 2569	Serpentina inox	Stainless steel water heating coil	Serpentin en acier inox
CA 2780	Adattatore scarico fumi su caldaie verticali per tubo Ø cm 15	Exhaust adapter on upright boilers for pipes Ø 15 cm	Adaptateur évacuation fumées sur chaudière verticale pour tuyau 15 cm diam
CA 2740	Polmone idraulico anti vibrazioni	Vibration-dampening hydraulic plenum chamber	Poumon hydraulique anti-belier

COD.	INCLUSO	INCLUDED	INCLUS
CA 1332	Tubo lancia mt. 10	10 mt. hose lance	Tube lance 10 mts.
CA 2760	Pistola con prolunga cm 37	Washing gun equipped with a 37 cm. extension	Pistolet avec rallonge 37 cm.
CA 2763	Terminale lancia cm 70	70 cm. lance end section	Section terminale lance 70 cm.
CARATTERISTICHE COSTRUTTIVE		TECHNICAL FEATURES	DETAILS TECHNIQUES
Detersivo in alta pressione con rubinetto dosaggio esterno		High pressure cleanser with external measuring tap	Détergent haute pression avec robinet de dosage externe
Alimentazione acqua in vaschetta lt 4		Water supply into the 4 lts tank	Alimentation eau dans le bac 4 lts.
Serbatoio detersivo incorporato lt 18		18 lts in-built cleanser tank	Réservoir détergent incorporé 18 lts.
Serbatoio gasolio incorporato lt. 35		35 lts in-built diesel tank	Réservoir gasoil incorporé 35 lts.
Regolatore di pressione esterno		Pressure control external gauge	Régulateur de pression externe
Versione (TST) Total Stop ritardato + stop mancanza acqua + livello controllo gasolio		TST Version delayed total stop + water lack stop + diesel level control	Version (TST) Total stop retardé + stop manque eau + niveau contrôle gasoil
Motore pompa con giunto elastico (no 165E/205E/225/305)		Pump motor with flexible coupling (no 165E-205E-225-305)	Moteur pompe avec joint élastique (no 165E 205E 225-305)

